

CV-CC2101 Series

Side Vision Camera



- Easy installation
- High performance digital image sensor
- IP67 weather-proof
- Vibration-proof
- Low power consumption
- IR LED irradiation distance is up to 7 meter
- Low illumination request under 0.1Lux

Specifications

Model	CV-CC2101	CV-CC2106	CV-CC210H	CV-CC210FH
Effective Pixel	756(H) x 504(V)	1297(H) x 977(V) approx. 1.27Mpixels	1280(H) x 960(V) approx. 1.27Mpixels	1920(H) x 1080(V)
SNR	47.1 dB	50 dB	44 dB	60 dB
HDR(WDR)	No	DWDR		
AHD Version	-		AHD2.0	
Signal Sync	Internal Sync.			
Video System	NTSC / PAL		AHD2.0	
Resolution	600 TV Line	700 TV Line	720P	1080P
Output I/F	Composite 1.0 Vp-p / 75 ohm			
Lens Focal / F No.	3.6 mm / F2.0			2.8 mm / F2.3
Lens Resolution	3M			
Lens View Angle (FOV)	V:56.2° H:75° D:93.7°		V:46.2° H:75° D:83.7°	V:58° H:108°
IR LED	7M (MAX)			5M
Microphone	No			
Video Mirror	Setting by factory			
Power Source	DC12V ± 10%			
Power Consumption	2.4W (MAX)			
Operation Temperature / Humidity	-20°C to 70°C (-4°F ~ 158°F)			
Stock Temperature / Humidity	-40°C to 85°C (-40°F ~ 185°F)			
Water-proof	IP67			
Anti-vibration	ISO16750-3 4.1.3.2.3			
Dimension	61.1(W) x 61.1(H) x 85.6(D)mm			
Weight	NW: 320g GW: 630g			
Connector	6 pin mini-din			

