

CV-CC2111 Series

Side Vision Camera



- Easy installation
- Small size
- High performance digital image sensor
- IP68 / IP69K weather-proof
- Vibration-proof
- Low power consumption
- IR LED irradiation distance 7 meter
- Low illumination request under 0.1Lux

Specifications

Model	CV-CC2111	CV-CC2116	CV-CC211H
Image Sensor	Pixelplus 1/3"	Sony 1/3.2"	1/3"
Effective Pixel	756(H) x 504(V)	1297(H) x 977(V) approx. 1.27Mpixels	1280(H) x 960(V) approx. 1.27Mpixels
Dynamic Range	62.9 dB	-	82 dB
SNR	47.1 dB	50 dB	44 dB
HDR(WDR)	No	DWDR	
AHD Version	-	AHD2.0	
Signal Sync	Internal Sync.		
Video System	NTSC / PAL		AHD2.0
Resolution	600 TV Line	700 TV Line	720P
Output I/F	Composite 1.0 Vp-p / 75 ohm		
Lens Focal / F No.	3.6 mm / F2.0		
Lens Resolution	3M		
Lens View Angle (FOV)	V:56.2° H:75° D:93.7°		V:46.2° H:75° D:83.7°
IR LED	7M (MAX)		
Microphone	Option		
Video Mirror	Setting by factory		
Fish eye correction (de-warping)	No		
Power Source	DC12V ± 10%		
Power Consumption	2.4W (MAX)		
Operation Temperature / Humidity	-20 to 70°C		
Stock Temperature / Humidity	-40 to 85°C		
Water-proof	IP68 / IP69K		
Anti-vibration	ISO16750-3 4.1.3.2.3		
Dimension	Ø46.9mm(W) x 50.5(H) x 83(D)mm		
Connector	6 pin mini-din		

