

CV-DC2201 Series

Inside Vision/Ceiling Mount Camera



- Easy installation
- High performance digital image sensor
- Vibration-proof
- Low power consumption
- IR LED irradiation distance is up to 4 meter
- Low illumination request under 0.1Lux

Specifications

Model	CV-DC2201	CV-DC220H	CV-DC220FH
Image Sensor	Pixelplus 1/3"	1/3"	1/2.9"
Effective Pixel	756(H) x 504(V)	1280(H) x 960(V) approx. 1.27Mpixels	1985(H) x 1105(V) approx. 2.19Mpixels
Dynamic Range	62.9 dB	82 dB	-
SNR	47.1 dB	44 dB	50 dB
HDR(WDR)	No	DWDR	-
AHD Version	-	AHD2.0	
Signal Sync	Internal Sync.		
Video System	NTSC / PAL	AHD2.0	
Resolution	600TV Line	720P	1080P
Output I/F	Composite 1.0 Vp-p / 75 ohm		
Lens Focal / F No.	2.3 mm / F2.0	2.1 mm / F2.0	
Lens Resolution	2M		
Lens View Angle (FOV)	H:128.3° V:91.6° D:176°	H:130° V:73° D:149°	H:120° V:87.3° D:160°
IR LED	4M (MAX)		
Microphone	Yes		
Video Mirror	Setting by factory		
Fish eye correction (de-warping)	No		
Power Source	DC12V ± 10%		
Power Consumption	2.4W (MAX)		
Operation Temperature / Humidity	-20 to 70°C		
Stock Temperature / Humidity	-40 to 85°C		
Water-proof	IPX1		
Anti-vibration	ISO16750-3 4.1.3.2.3		
Dimension	57(H) x Ø69(D)mm		
Weight	NW : 224g		
Connector	6 pin mini-din		

