

CV-MR422S CV-MR422N

4CH 1080P H.265 Mobile DVR



- H.265 high performance video compression
- GPS/G-Sensor Logging and event triggering
- Support built in 4G/Wi-Fi (CV-MR422N)
- Build in backup power (Option)
- Record rate 30fps/1080P
- 4CH Full HD (Downward compatible), 4CH Sound input
- Storage: Up to 256GB * 2 SD card (SDXC)
- Anti-vibration design
- Trigger Output 12V
- Support power output to cameras
- Trigger the image: CH 1 ~ CH 3
- Ignition-off record
- Wide range DC 8V ~ 36V power input
- Surge protection design
- Windows AP: including Playback, e-map, G-sensor information, print, and search functions

Specifications

Model	CV-MR422S	CV-MR422N
System	AHD / TVi / NTSC / PAL	
Video compression format	H.265 main profile	
Video / Audio Input	4CH	
Video out	RCA x1	
Audio out	RCA x1	
S/N Ratio	> 40dB	
Screen display	1/2/3/4	
Live Resolution	Vedio out :NTSC:720(H) x 480(V) ; PAL :720(H) x 576(V) ; HD out :1920(H) x 1080(V)	
Recording Resolution	D1: 702x480(NTSC); 702x576(PAL), 960H/720P/1080P	
Recording Frame Rate	D1: 30fps per Channel (NTSC) / 25fps per Channel (PAL) 960H/720P/1080P: 30fps/25fps	
Recording Quality	Low / Middle / High	
Recording Mode	Automatically overwrite	
Multi-task	Live / Record / Play	Live / Record / Play / Network
Di Input /DC 12V Out	Di X3 / DC 12V x 1	
External indicator light	Optional	
USB	USB2.0 x 1	
Storage	SDXC SD x 2 up to 256GB	
Language	English / Chinese / Japanese	
Monitor	N/A	4G Mobile phone (iPhone / iPad / Window Mobile / Android)
IR remote control	Standard	
GPS	G - Mouse Type, supports protocol: NMEA 0183	
G Sensor	3 Axis G - force sensor	
Browse the way	N/A	Remote software VMS (64CH)
Network Protocol	N/A	DHCP / HTTP / TCP / IP / SMTP / RTP / RSTP
Remote control	N/A	Monitor / Playback / Backup / DVR control / GPS / Map
Anti-vibration	ISO16750 - 3	
Shock-proof	Yes	
Power	DC 8~36V	
Operating Temperature	-10 to 60°C (w/o SD card)	
Operating Humidity	Less than 90%	
Dimension	135 (W) x 40 (H) x 170 (D) mm	
4G	N/A	LTE

