

CV-TM7721

Screening Attendance Device

- 8 inch LCD touch screen
- Human-sounding voice prompt in multiple languages
- Support tampering Alarm
- Support DI /DO and Wiegand interface
- Support Watchdog to ensure the operation stability
- IP65 ingress protection



Specifications

Screen	
LCD Screen	8-inch touch display screen ; contrast: 500:1
Screen Resolution	1280 x 800
Brightness	500 lux
Control Interface	I2C
Thermal Camera (Optional)	
Temperature Measuring Range	32~43° C
Accuracy	± 0.3° C
Measuring Distance	30~50cm
Camera	
Image Sensor	1 / 2.8" CMOS
Image Size	1920 x 1080
Lens	Dual-lens, f=3.97mm @ F1.6
WDR	120dB
Day & Night	Light soft white light, IR light
IR Distance	10m
White Light Distance	1-3m
Audio	
Audio compression	G.711A / U
Two-way audio	Yes (noise reduction and echo cancellation)
Interfaces	
Network	RJ45 100Mbps x 1
RS 485	RS485x1 (half duplex)
USB	USB x1
Video Output	-
Audio line in / out	Built-in MIC / built-in speaker
Alarm Input / Output	2 CH / 2 CH
Wiegand	Wiegand input/output (26/34)
Door Lock Output	Relay output, NO/NC(optional), delay setting supported
Anti-Tamper	1 button
Exit Button	1 button
Reset Button	1 button
Storage	
SD card	Built-in micro SD card slot; up to 128GB

